



SECTION 1: IDENTIFICATION

- 1.1 Product identifier: Diesel Defender
Other means of identification:
Not applicable
- 1.2 Recommended use of the chemical and restrictions on use:
Relevant uses (Consumer use): Diesel Additive
Relevant uses (Professional users): Diesel Additive
Relevant uses (Industrial user): Diesel Additive
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Initial supplier identifier:
R.B. Howes & Co. Inc.
60 Ocean State Drive
02852 North Kingstown - RI - United States
Phone: 4012945500
SDS@howesproducts.com
www.howesproducts.com
- | <u>Manufacturer</u> | <u>Distributor</u> |
|---|---|
| R.B. Howes & Co., Inc.
3511 North Ohio Street
Wichita, KS, 67219
USA
T 401-294-5500, 1-800 GET HOWES (438-4693) | White Line Distributors
3625 Weston Rd Unit 24
North York, ON M9L 1V9 - Canada
T +1 416-747-8509 |
| <u>Manufacturer</u>
EMCO Chemical Packaging
2100 Commonwealth Ave.
North Chicago, IL 60064 - USA
T 847-689-2200 | <u>Distributor</u>
Associated Truckers Supply
44195 Yale Rd
Chilliwack, BC V2R 4H2 - Canada
T +1 604-795-5700 |
- 1.4 Emergency phone number: 703-527-3887
(CHEMTREC) 800-424-9300

SECTION 2: HAZARD IDENTIFICATION

2.1 Classification of the substance or mixture:

Classified in accordance with 29 CFR 1910.1200 (HCS 2024) and Part 2 of the Canadian Hazardous Products Regulations (HPR), as amended.

29 CFR 1910.1200 / WHMIS 2022:

Acute Tox. 4: Acute inhalation toxicity, Category 4, H332
Asp. Tox. 1: Aspiration hazard, Category 1, H304
Carc. 2: Carcinogenicity, Category 2, H351
Flam. Liq. 4: Flammable liquids, Category 4, H227
Skin Irrit. 2: Skin irritation, Category 2, H315
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:



Signal word: Danger

Required workplace pictograms: Exclamation mark; Health hazard

Hazard statements:

H332 Harmful if inhaled.
H304 May be fatal if swallowed and enters airways.
H351 Suspected of causing cancer.
H227 Combustible liquid.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapors or mist.
P264 Wash hands and exposed skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves and eye protection. Use face protection where splash exposure is possible.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P331 Do NOT induce vomiting.
P302+P352 IF ON SKIN: Wash with plenty of water.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.



Safety data sheet
According to 29 CFR 1910.1200 (HCS 2024) and WHMIS
2022 (SOR/2022-272)
Diesel Defender

P308+P313 IF exposed or concerned: Get medical advice/attention.
P370+P378 In case of fire: Use foam, dry chemical powder or carbon dioxide to extinguish.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/container in accordance with applicable local, regional, national and international regulations.

2.3 Hazards not otherwise classified / Other hazards:

United States - Hazards associated with known or reasonably anticipated uses resulting from chemical reactions under 29 CFR 1910.1200(d)(1)(ii): None identified.

United States - Hazards not otherwise classified (HNOC): Non-applicable.

Canada - Health and physical hazards not otherwise classified (HHNOC - PHNOC): Not available.

Canada - Other hazards known to the supplier: None identified.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances: Not applicable (mixture).

3.2 Mixtures: Mixture composed of additives in solvents.

CAS / unique identifier	Chemical name	Concentration (% w/w)
8008-20-6	Kerosine (petroleum)	30-60%*
64742-47-8	Distillates (petroleum), hydrotreated light	10-30%*
64742-53-6	Distillates (petroleum), hydrotreated light naphthenic, <3% IP 346, <20.5 cSt @ 40°C	10-30%*
64742-94-5	Solvent naphtha (petroleum), heavy aromatic	10-30%*
Withheld / not available; Health Canada HMIRA Registry No. 3829212	Long Chain Alkenyl Acid	1-5%*
95-63-6	1,2,4-Trimethylbenzene	1-5%*
64742-95-6	Solvent naphtha (petroleum), light aromatic, <0.1% EC 200-753-7	1-5%*
104-76-7	2-Ethylhexanol	1-5%*
91-20-3	Naphthalene	1-5%*
98-94-2	Cyclohexyldimethylamine	<1%*

* Actual concentration or concentration range is withheld as confidential business information / trade secret. Canadian prescribed concentration ranges are used where applicable. Specific chemical identity for the Long Chain Alkenyl Acid is protected under Health Canada HMIRA Registry No. 3829212 (filing date 2025-12-31). Confidential identity and/or exact concentration information is withheld as a trade secret in accordance with 29 CFR 1910.1200(i).

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

Inhalation: Remove person to fresh air and keep comfortable for breathing. If symptoms are significant or persist, call a POISON CENTER or doctor. If breathing has stopped, trained personnel should provide appropriate resuscitation and obtain emergency medical assistance.

Skin contact: Remove contaminated clothing and footwear. Wash affected skin with plenty of water and soap. If skin irritation occurs, get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses if present and easy to do. Continue rinsing. Obtain medical advice if irritation persists.

Ingestion / aspiration: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. If vomiting occurs spontaneously, keep the head below the hips to reduce aspiration risk. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms/effects, acute and delayed: Skin irritation; harmful effects if inhaled; central nervous system effects including drowsiness or dizziness; aspiration into the lungs may be fatal. See Sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment: Aspiration hazard requires prompt medical evaluation following ingestion.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable extinguishing media: Foam, dry chemical powder, or carbon dioxide.

Unsuitable extinguishing media: Do not use a direct water jet.

5.2 Specific hazards arising from the chemical: Combustible liquid. Thermal decomposition and combustion can generate carbon monoxide, carbon dioxide and other irritating or toxic organic decomposition products.

5.3 Special protective equipment and precautions for fire-fighters: Wear full protective clothing and self-contained breathing apparatus. Evacuate nonessential personnel, remove ignition sources, and cool exposed containers with water spray from a safe distance where appropriate. Prevent fire-fighting runoff from entering waterways.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures: Evacuate unnecessary personnel. Eliminate ignition sources. Provide adequate ventilation. Prevent formation of flammable vapor-air mixtures. Wear appropriate PPE as described in Section 8. Ground and bond conductive equipment where static accumulation is possible.

6.2 Environmental precautions: Prevent entry into drains, sewers, surface water and groundwater. Contain released material. Notify the appropriate authority if a release threatens the public or environment.

6.3 Methods and materials for containment and cleaning up: Absorb with sand or other inert noncombustible absorbent and place in suitable closed containers for disposal. Do not use sawdust or other combustible absorbents. For releases to water, use barriers or other appropriate containment and mechanical recovery methods; obtain required approvals before using dispersants.

United States reporting: For releases exceeding applicable reportable quantities, refer to 40 CFR 302 and notify the National Response Center at 800-424-8802 as required.

6.4 Reference to other sections: See Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling: Keep containers tightly closed. Avoid skin contact and breathing vapors/mist. Use adequate ventilation. Keep away from ignition sources. Transfer slowly and ground/bond equipment where static accumulation is possible. Do not eat, drink or smoke while handling; wash after use. Follow applicable U.S. and Canadian occupational health and safety requirements.

7.2 Conditions for safe storage, including incompatibilities: Store in a cool, dry, well-ventilated location. Keep container tightly closed and locked up. Protect from heat, ignition sources, direct sunlight, static discharge and incompatible materials. Keep away from food.

7.3 Specific end use(s): Diesel additive. No additional recommendations beyond those specified in this SDS.



Safety data sheet
According to 29 CFR 1910.1200 (HCS 2024) and WHMIS
2022 (SOR/2022-272)
Diesel Defender

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substance	U.S. OSHA PEL	ACGIH TLV (2026)	British Columbia	Alberta	Ontario
Kerosine (petroleum) (8008-20-6)	--	200 mg/m ³ TWA	200 mg/m ³ TWA	200 mg/m ³ 8-h	--
1,2,4-Trimethylbenzene (95-63-6)	--	10 ppm TWA	25 ppm TWA	25 ppm (123 mg/m ³) 8-h	--
Mesitylene (108-67-8)	--	10 ppm TWA	25 ppm TWA	25 ppm (123 mg/m ³) 8-h	--
Cumene (98-82-8)	50 ppm (245 mg/m ³) TWA	5 ppm TWA	25 ppm TWA; 75 ppm STEL	50 ppm (246 mg/m ³) 8-h	--
Naphthalene (91-20-3)	10 ppm (50 mg/m ³) TWA	10 ppm TWA	10 ppm TWA	10 ppm (52 mg/m ³) 8-h; 15 ppm (79 mg/m ³) 15-min	--
Cyclohexyldimethylamine (98-94-2)	--	--	--	--	5 ppm (26 mg/m ³) STEL

8.2 Appropriate engineering controls: Use process enclosure, local exhaust ventilation or general dilution ventilation as needed to maintain airborne concentrations below applicable occupational exposure limits. Conduct a workplace hazard assessment and select controls appropriate to the task and jurisdiction.

Respiratory protection: Where engineering controls cannot maintain airborne concentrations below applicable limits or acceptable levels, use a NIOSH-approved or otherwise jurisdictionally approved respirator selected by a qualified professional and used under an appropriate respiratory protection program.

Hand protection: Wear chemical-resistant protective gloves suitable for hydrocarbon/solvent exposure. Select glove material and breakthrough time based on the specific task and manufacturer data.

Eye/face protection: Wear safety glasses with side shields. Use chemical splash goggles and/or a face shield where splash exposure is possible.

Body protection: Wear protective clothing as needed to prevent skin contact. Remove and launder contaminated clothing before reuse.

Environmental exposure controls: Prevent uncontrolled release to the environment. Use containment where spills could enter drains or waterways.

Volatile organic compounds (VOC): 73.63% by weight

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Property	Value
Physical state	Liquid
Appearance	Dark Amber/Brown
Color / colour	Dark Amber/Brown
Odor / odour	Characteristic
Odor threshold	Not available
Melting point/freezing point	Not available
Boiling point / initial boiling point / range	Not available
Flammability	Combustible liquid
Lower/upper flammability or explosive limits	Not available
Flash point	>66 °C (>150 °F)
Autoignition temperature	Not available
Decomposition temperature	Not available
pH	Not available
Kinematic viscosity	≤20.5 mm ² /s at 40 °C (104 °F)
Solubility in water	Insoluble
Partition coefficient (n-octanol/water)	Not available
Vapor pressure	Not available
Relative vapor density	Not available
Relative density	0.86 at 20 °C / 68 °F
Particle characteristics	Not applicable - liquid

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity: No hazardous reactions are expected under recommended storage and handling conditions.

10.2 Chemical stability: Stable under recommended conditions.

10.3 Possibility of hazardous reactions: Hazardous polymerization or reactions producing excessive temperature or pressure are not expected under recommended conditions.

10.4 Conditions to avoid: Heat, ignition sources, direct sunlight, static discharge and conditions that could create combustible vapor-air mixtures.

10.5 Incompatible materials: Strong acids, strong bases and strong oxidizing materials.

10.6 Hazardous decomposition products: Carbon monoxide, carbon dioxide and other organic decomposition products may be generated during combustion or thermal decomposition.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects: Product-specific experimental toxicological data are not available. The assessment below is based on available ingredient information and applicable mixture classification principles.

Likely routes of exposure: Inhalation, skin contact and ingestion. Eye exposure may occur from splashes.

Symptoms related to physical, chemical and toxicological characteristics: High vapor concentrations may cause headache, dizziness, nausea, confusion and, in severe cases, loss of consciousness. Skin contact causes irritation. Aspiration into the lungs following ingestion may cause severe lung injury and may be fatal.

Delayed and immediate effects; chronic effects: This product is classified as Carcinogenicity Category 2: Suspected of causing cancer. Based on available data, criteria for mutagenicity, reproductive toxicity, sensitization and STOT-repeated exposure are not met.

Substance	Oral	Dermal	Inhalation
Kerosine (petroleum)	LD50 oral 5500 mg/kg (rat)	LD50 dermal 5500 mg/kg (rabbit)	LC50 inhalation: not available
Solvent naphtha, light aromatic	LD50 oral 2100 mg/kg (rat)	LD50 dermal 2000 mg/kg (rabbit)	LC50 inhalation: not available
Solvent naphtha, heavy aromatic	LD50 oral >5000 mg/kg	LD50 dermal >5000 mg/kg	LC50 inhalation: not available
Cyclohexyldimethylamine	LD50 oral 289 mg/kg (rat)	LD50 dermal 380 mg/kg (rat)	LC50 inhalation 3 mg/L
1,2,4-Trimethylbenzene	LD50 oral 3400 mg/kg (rat)	LD50 dermal 3160 mg/kg (rabbit)	LC50 inhalation 10.2 mg/L (rat)
2-Ethylhexanol	LD50 oral 2047 mg/kg (rat)	LD50 dermal: not available	LC50 inhalation 11 mg/L
Naphthalene	LD50 oral 533 mg/kg (rat)	LD50 dermal 16000 mg/kg (rat)	LC50 inhalation: not available



Safety data sheet
According to 29 CFR 1910.1200 (HCS 2024) and WHMIS
2022 (SOR/2022-272)
Diesel Defender

Mixture inhalation acute toxicity: Classified as Acute Toxicity (Inhalation) Category 4 (H332). Calculated mixture ATE: Not available.

Interactive effects: No relevant interaction information is readily available.

Carcinogenicity listings: Cumene and Naphthalene are identified in NTP / regulatory carcinogen information and California Proposition 65 cancer listings. No OSHA specifically regulated carcinogen is identified.

Alternative information / methodology: Where product-specific data are unavailable, classification and toxicological conclusions are based on available component data, read-across where appropriate, and the mixture classification rules applicable under HCS 2024 and the HPR.

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Acute toxicity:

Identification			Species	Genus
Kerosine (petroleum)	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
Distillates (petroleum), hydrotreated light	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
1,2,4-trimethylbenzene	LC50	7.72 mg/L (96 h)	Pimephales promelas	Fish
	EC50	6.14 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Not available		
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
2-ethylhexanol	LC50	17.1 mg/L (96 h)	N/A	Fish
	EC50	39 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	21 mg/L (72 h)	Desmodesmus subspicatus	Algae
Naphthalene	LC50	1.6 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	2.2 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Not available		
Cyclohexyldimethylamine	LC50	28 mg/L (96 h)	Leuciscus idus	Fish
	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	2 mg/L (72 h)	Desmodesmus subspicatus	Algae

Chronic toxicity:

Identification			Species	Genus
Naphthalene	NOEC	0.37 mg/L	Oncorhynchus kisutch	Fish
	NOEC	0.59 mg/L	Daphnia pulex	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification		Degr	Biodegradab	
1,2,4-trimethylbenzene	BOD5	Not available	Concentration	100 mg/L
	COD	Not available	Period	28 days
	BOD5/COD	Not available	% Biodegradable	18 %
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7	BOD5	0.19 g O2/g	Concentration	Not available
	COD	0.44 g O2/g	Period	Not available
	BOD5/COD	0.43	% Biodegradable	Not available
Naphthalene	BOD5	Not available	Concentration	Not available
	COD	Not available	Period	28 days
	BOD5/COD	Not available	% Biodegradable	74 %
Cyclohexyldimethylamine	BOD5	Not available	Concentration	20 mg/L
	COD	Not available	Period	28 days
	BOD5/COD	Not available	% Biodegradable	95 %

SECTION 12: ECOLOGICAL INFORMATION (continued)

12.3 Bioaccumulative potential:



Safety data sheet
According to 29 CFR 1910.1200 (HCS 2024) and WHMIS
2022 (SOR/2022-272)
Diesel Defender

Substance-specific information:

Identification	Bioaccumulation	
Kerosine (petroleum)	BCF	5800
	Pow Log	5.25
	Potential	Very High
Distillates (petroleum), hydrotreated light	BCF	130
	Pow Log	3.3
	Potential	High
Solvent naphtha (petroleum), heavy arom	BCF	159
	Pow Log	4.5
	Potential	High
1,2,4-trimethylbenzene	BCF	154
	Pow Log	3.78
	Potential	High
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7	BCF	
	Pow Log	4
	Potential	
2-ethylhexanol	BCF	20
	Pow Log	2.9
	Potential	Low
Cyclohexyldimethylamine	BCF	
	Pow Log	2.31
	Potential	

12.4 Mobility in soil:

Identification	Absorption		Volatility	
1,2,4-trimethylbenzene	Koc	537	Henry	624.16 Pa·m ³ /mol
	Conclusion	Low	Dry soil	Yes
	Surface tension	2.919E-2 N/m (25 °C)	Moist soil	Yes
2-ethylhexanol	Koc	62	Henry	Not available
	Conclusion	High	Dry soil	Not available
	Surface tension	2.82E-2 N/m (25 °C)	Moist soil	Not available
Naphthalene	Koc	Not available	Henry	Not available
	Conclusion	Not available	Dry soil	Not available
	Surface tension	1.306E-2 N/m (277.74 °C)		Not available
Cyclohexyldimethylamine	Koc	69.49	Henry	6.73 Pa·m ³ /mol
	Conclusion	High	Dry soil	Not available
	Surface tension	Not available	Moist soil	Not available

12.5 Results of PBT and vPvB assessment:

Not available

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods: Do not discharge product or waste to drains. Dispose of product, contaminated absorbents and containers through an authorized waste service in accordance with applicable federal/national, state/provincial and local requirements. Empty containers may retain hazardous residues.

United States: Evaluate waste under the RCRA framework and applicable EPA requirements; state requirements may be more stringent. Household wastes generated by normal household activities are excluded as described in 40 CFR 261.4.

Canada: Manage waste in accordance with applicable federal/provincial requirements, including the Canadian Environmental Protection Act, 1999 where applicable.

SECTION 14: TRANSPORT INFORMATION

14.1-14.7 United States - U.S. DOT / 49 CFR:

Item	U.S. DOT information
Identification number	NA1993
Proper shipping name	Combustible liquid, n.o.s. (Kerosine (petroleum); Distillates (petroleum), hydrotreated light)
Hazard class	Combustible Liquid
Packing group	III
Marine pollutant	Yes
Special provisions	49 CFR 173.150 may allow non-hazardous treatment for certain non-bulk containers under 120 gallons; marine-pollutant requirements may not apply to specified non-bulk highway/rail/air shipments under 49 CFR 171.4.



Safety data sheet
According to 29 CFR 1910.1200 (HCS 2024) and WHMIS
2022 (SOR/2022-272)
Diesel Defender

Canada - TDG:

Item	Canada TDG information
UN number	UN3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tolyltriazole; Kerosine (petroleum))
Class	9
Packing group	III
Environmental hazard	Yes

Sea - IMDG 42-24: UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tolyltriazole; Kerosine (petroleum)); Class 9; PG III; Marine pollutant: Yes; EmS F-A, S-F; limited quantity 5 L; special provisions 375, 335, 274, 969.

Air - IATA/ICAO 2026: UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tolyltriazole; Kerosine (petroleum)); Class 9; PG III; environmental hazard: Yes.

Transport limitations: This product is not packaged or prepared for transport in accordance with IMDG or IATA/ICAO requirements and is not intended to be shipped by sea or air.

SECTION 15: REGULATORY INFORMATION

15.1 United States:

- OSHA specifically regulated substances (29 CFR 1910.1001-1096): Non-applicable.
- Toxic Substances Control Act (TSCA): All components are listed or exempt.
- EPCRA Section 313 (40 CFR Part 372): 1,2,4-Trimethylbenzene (95-63-6); Cumene (98-82-8); Naphthalene (91-20-3).
- CERCLA reportable substances: Cumene (98-82-8) - U055; Naphthalene (91-20-3) - U165.
- Clean Air Act hazardous air pollutants: Cumene (98-82-8); Naphthalene (91-20-3).
- California Proposition 65 - Cancer: Cumene (98-82-8); Naphthalene (91-20-3).
- California Proposition 65 - Birth defects or other reproductive harm: Non-applicable.
- California Labor Code - Hazardous Substances List: 1,2,4-Trimethylbenzene (95-63-6); Cumene (98-82-8); Naphthalene (91-20-3).
- Massachusetts RTK - Substance List: Kerosine (petroleum); distillates (petroleum), hydrotreated light naphthenic; solvent naphtha (petroleum), light aromatic; 1,2,4-trimethylbenzene; hydrocarbons, C10-C13, aromatics, >1% naphthalene; cumene; naphthalene.
- Pennsylvania Worker and Community Right-to-Know Law: Kerosine (petroleum); distillates (petroleum), hydrotreated light naphthenic; solvent naphtha (petroleum), light aromatic; hydrocarbons, C10-C13, aromatics, >1% naphthalene; naphthalene.
- Rhode Island - Hazardous substances RTK: Cumene (98-82-8); Naphthalene (91-20-3).

15.1 Canada:

- Domestic Substances List (DSL): Disclosed components are listed as applicable.
- National Pollutant Release Inventory (NPRI) 2025-2027: light aromatic solvent naphtha, 1,2,4-trimethylbenzene, cumene, naphthalene, heavy aromatic solvent naphtha and hydrotreated light distillates.
- First Priority Substances List (PSL1): Naphthalene.
- Toxic substances list - Part 2: Naphthalene.
- Canadian Environmental Protection Act, 1999.
- Canada WHMIS Confidential Business Information: HMIRA Registry No. 3829212; filing date 2025-12-31.
- Other federal, state/provincial and local requirements may apply.

SECTION 16: OTHER INFORMATION

Regulatory basis: Prepared to address the information requirements of 29 CFR 1910.1200, including Appendices C and D (HCS 2024), and Part 4 / Schedule 1 of the Canadian Hazardous Products Regulations, including amendments under SOR/2022-272.

Principal references:

- Occupational Safety and Health Administration (OSHA), 29 CFR 1910.1200 and Appendices C/D.
- Health Canada, Workplace Hazardous Materials Information System (WHMIS) / Hazardous Products Regulations supplier guidance.
- United Nations, Globally Harmonized System of Classification and Labelling of Chemicals (GHS), 7th Revised Edition.

Date of compilation: 2025-12-05

Revision date: 2026-08-24

Disclaimer: The information contained in this safety data sheet is based on sources, technical knowledge and current legislation. This information cannot be considered a guarantee of the properties of the product; it is a description of the safety requirements. The occupational methodology and conditions of use are outside the supplier's direct control. The information in this SDS refers only to this product and the uses specified herein.