



Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 2017-03-08
Revision date: 2024-02-23
Supersedes: 2021-07-13
Version: 3.3

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Diesel Treat
Product code : 103060, 103061, 103062, 103064, 103065, 103066, 103068, 103070, 103089

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Diesel Fuel Additive

1.3. Supplier

Manufacturer

R.B. Howes & Co., Inc.
3511 North Ohio Street
Wichita, KS 67219 - USA
T 401-294-5500, 1-800 GET HOWES (438-4693)

1.4. Emergency telephone number

Emergency number : CHEMTREC 1 (800) 424-9300 / 703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Liq. 4
Skin Irrit. 2
Carc. 2
Repr. 2
Asp. Tox. 1

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Combustible liquid
May be fatal if swallowed and enters airways.
Causes skin irritation.
Suspected of causing cancer.
Suspected of damaging the unborn child.

Precautionary statements (GHS) :

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Wash hands, forearms and face thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If exposed or concerned: Get medical advice/attention.
If swallowed: Immediately call a poison center or doctor.

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Do NOT induce vomiting.
If on skin: Wash with plenty of water.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Distillates, petroleum, hydrotreated light naphthenic	Distillates, petroleum, hydrotreated light naphthenic Petroleum distillates, hydrotreated light naphthenic / Mineral oil, petroleum distillates, hydrotreated light naphthenic / Distillates (petroleum), hydrotreated light naphthenic / Distillates (petroleum) hydrotreated light naphthenic	CAS-No.: 64742-53-6	30 - 60
Kerosine, petroleum	Kerosine, petroleum DEODORIZED KEROSENE / Kerosine (petroleum) / Kerosine / Kerosene / Kerosine, petroleum (Straight Run, Kerosene (petroleum). A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C9-16 and boiling in the range of approximately 180-300°C.) / Kerosene, jet fuel / Kerosene, jet fuels / Kerosine fraction petroleum / Lamp oil / Kerosene/Jet fuels / Navy Fuels JP-5 / kerosene / Kerosenes (including jet fuels) / Kerosine (petroleum); Straight run kerosine [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (320°F to 554°F).]	CAS-No.: 8008-20-6	15 - 40

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Name	Chemical name / Synonyms	Product identifier	%
Solvent naphtha, petroleum, light aromatic	Solvent naphtha, petroleum, light aromatic Light aromatic solvent naphtha (petroleum) (C8-10) / Solvent naphtha, petroleum, light aromatic (A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8-10 and boiling in the range of approximately 135-210°C.) / Aromatic naphtha, type I / Solvent naphtha (petroleum), light aromatic, hydrotreated / Hydrocarbons, C9, aromatics / Solvent naphtha (petroleum), light aromatic; Low boiling point naphtha -unspecified [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] / Aromatic hydrocarbon solvents - medium flashpoint / solvent naphtha (petroleum, light aromatic) / Solvent naphtha, petroleum, light aromatic-low boiling point hydrogen treated naphtha / Aromatic 100 / Light aromatic solvent naphtha / Solvent naphtha (petroleum), light aromatic	CAS-No.: 64742-95-6	1 - 5
Benzene, 1,2,4-trimethyl-	Benzene, 1,2,4-trimethyl- Pseudocumene / 1,2,4-Trimethylbenzene / Trimethylbenzene, 1,2,4- / Trimethylbenzene	CAS-No.: 95-63-6	1 - 5
Amides, C16-18 and C18-unsaturated, N,N-bis(hydroxyethyl)	Amides, C16-18 and C18-unsaturated, N,N-bis(hydroxyethyl) SDA 11-024-00 / N,N-Bis(hydroxyethyl)-fatty(C16-18 and C18 unsaturated) amides	CAS-No.: 68603-38-3	0.5 – 1.5
Solvent naphtha, petroleum, heavy aromatic	Solvent naphtha, petroleum, heavy aromatic Naphtha (petroleum), heavy aromatic / Heavy aromatic naphtha / Solvent naphtha (petroleum), heavy aromatic / Heavy aromatic solvent naphtha / Aromatic 150 / Solvent naphtha (petroleum) heavy aromatic / Heavy aromatic solvent naphtha (petroleum) / Solvent naphtha, petroleum, heavy aromatic (A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C9-16 and boiling in the range of approximately 165-290°C.) / Solvent naphtha / Hydrocarbons, C10-13, aromatics, >1% naphthalene / Solvent naphtha (petroleum), heavy aromatic; Kerosine - unspecified [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 165°C to 290°C (330°F to 554°F).] / Solvent naphtha (petroleum), heavy arom. / Solvent naphtha heavy aromatic	CAS-No.: 64742-94-5	0.1 - 1

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Name	Chemical name / Synonyms	Product identifier	%
Xylenes (o-, m-, p- isomers)	Xylenes (o-, m-, p- isomers) Benzene, dimethyl- / Dimethylbenzene (mixed isomers) / Xylene / Xylene (all isomers) / Xylene (mixed isomers) / Xylene (o-, m-, p- isomers) / Xylenes / Xylenes (mixed isomers) / Dimethylbenzene / Xylol / Benzene, dimethyl-, mixed isomers / XYLENE / Dimethylbenzenes / Xylene isomers mixture / Dimethylbenzene (2-, 3-, 4-isomers) / Dimethylbenzene (mixed 2-, 3-, 4-isomers) / C8 Disubstituted benzenes / Xylene, mixed isomers / Xylenes (meta-, ortho-, para-) / Xylene (mixture), including m-xylene, o-xylene, p-xylene / Xylene (o-,m-,p- isomer mixture)	CAS-No.: 1330-20-7	0.1 - 1
Naphthalene	Naphthalene Naphthalene, molten / Naphthalene, crude / Naphthalenes / Moth balls	CAS-No.: 91-20-3	0.1 - 1
Isopropylbenzene	Isopropylbenzene 2-Phenylpropane / (1-Methylethyl)benzene / Benzene, (1-methylethyl)- / Cumene	CAS-No.: 98-82-8	0.1 - 1
Ethylbenzene	Ethylbenzene Benzene, ethyl- / ETHYLBENZENE / Phenylethane	CAS-No.: 100-41-4	0.1 - 1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause stomach distress, nausea or vomiting.
Chronic symptoms	: Suspected of causing cancer. Suspected of damaging the unborn child.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Carbon dioxide. Water fog.
Unsuitable extinguishing media : Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid. Products of combustion may include, and are not limited to: oxides of carbon. Irritating vapours.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Move containers away from the fire area if this can be done without risk. Cool closed containers exposed to fire with water spray.
Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate sources of ignition. Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Remove ignition sources. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation. Spilled material may present a slipping hazard.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Handle and open container with care.
Hygiene measures : Take off contaminated clothing and wash it before reuse. Always wash hands after handling the product.

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Subject to 29 CFR § 1910.106.
Storage conditions	: Keep out of the reach of children. Keep container tightly closed. Keep cool. Store in a dry, cool and well-ventilated place. Store locked up.
Incompatible materials	: Refer to Section 10 on Incompatible Materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Diesel Treat	
No additional information available	
Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)	
No additional information available	
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
No additional information available	
Naphthalene (91-20-3)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	10 ppm
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans, Skin - potential significant contribution to overall exposure by the cutaneous route
USA - ACGIH - Biological Exposure Indices	
BEI	Parameter: 1-Naphthol with hydrolysis plus 2-Naphthol with hydrolysis - Sampling time: end of shift (nonquantitative, nonspecific)
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	50 mg/m ³
OSHA PEL TWA	10 ppm
USA - IDLH - Occupational Exposure Limits	
IDLH	250 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	50 mg/m ³
NIOSH REL TWA	10 ppm
NIOSH REL STEL	75 mg/m ³
NIOSH REL STEL	15 ppm
Xylenes (o-, m-, p- isomers) (1330-20-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift (technical or commercial grade)

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Xylenes (o-, m-, p- isomers) (1330-20-7)	
USA - OSHA - Occupational Exposure Limits	
Local name	Xylenes (o-, m-, p-isomers)
OSHA PEL TWA	435 mg/m ³
OSHA PEL TWA	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Ethylbenzene (100-41-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA - ACGIH - Biological Exposure Indices	
BEI	0.15 g/g creatinine Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: end of shift (nonspecific)
USA - OSHA - Occupational Exposure Limits	
Local name	Ethyl benzene
OSHA PEL TWA	435 mg/m ³
OSHA PEL TWA	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1 OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	800 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	435 mg/m ³
NIOSH REL TWA	100 ppm
NIOSH REL STEL	545 mg/m ³
NIOSH REL STEL	125 ppm
Kerosine, petroleum (8008-20-6)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	200 mg/m ³ (application restricted to conditions in which there are negligible aerosol exposures- total hydrocarbon vapor (Kerosene/Jet fuels)
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans, Skin - potential significant contribution to overall exposure by the cutaneous route
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	100 mg/m ³
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
No additional information available	
Benzene, 1,2,4-trimethyl- (95-63-6)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	10 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Benzene, 1,2,4-trimethyl- (95-63-6)	
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	125 mg/m ³
NIOSH REL TWA	25 ppm
Isopropylbenzene (98-82-8)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Cumene
ACGIH OEL TWA	5 ppm
Remark (ACGIH)	TLV® Basis: URT adenoma; neurological eff. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Cumene
OSHA PEL TWA	245 mg/m ³
OSHA PEL TWA	50 ppm
Limit value category (OSHA)	prevent or reduce skin absorption
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	900 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	245 mg/m ³
NIOSH REL TWA	50 ppm
US-NIOSH chemical category	Potential for dermal absorption
Amides, C16-18 and C18-unsaturated, N,N-bis(hydroxyethyl) (68603-38-3)	
No additional information available	

Exposure limit values for the other components

Benzene (71-43-2)	
USA - OSHA - Occupational Exposure Limits	
Local name	Benzene
OSHA PEL TWA	10 ppm 1 ppm
OSHA PEL STEL	5 ppm (see 29 CFR 1910.1028)
OSHA PEL C	25 ppm
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	50 ppm Peak (10 minutes)

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Benzene (71-43-2)

Remark (OSHA)	Benzene is subject to the standard 29 CFR 1910.1028 which may contain specific requirements for handling including protective equipment, regulated areas, monitoring and medical surveillance. The employer should review the standard and assure compliance with applicable requirements.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-2

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available.
Colour	: Light amber
Odour	: Distinctive
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 164 °C (327 °F)
Flash point	: > 148 °F (>= 148 °F) [Closed cup]
Relative evaporation rate (butylacetate=1)	: No data available
Flammability	: Combustible liquid.
Vapour pressure	: < 0.1 mm Hg
Relative vapour density at 20°C / 68 °F	: > 1 (air = 1)
Relative density	: < 0.9 (water = 1)
Solubility	: Insoluble.
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Viscosity, kinematic	: 3.89 mm ² /s @ 40 °C (104 °F)
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal conditions. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Sources of ignition. Incompatible materials.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Flammable gases. Irritating vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	2180 mg/m ³ (Exposure time: 4 h)
ATE CA (vapours)	2.18 mg/l/4h
ATE CA (dust,mist)	2.18 mg/l/4h
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Remarks on results: other:
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: other:

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Remarks on results: other:
LC50 inhalation rat	> 590 mg/m ³ (Exposure time: 4 h)
Naphthalene (91-20-3)	
LD50 oral rat	1110 mg/kg
LD50 dermal rabbit	1120 mg/kg
LC50 inhalation rat	> 0.4 mg/l/4h
ATE CA (oral)	1110 mg/kg bodyweight
ATE CA (Dermal)	1120 mg/kg bodyweight
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	> 4350 mg/kg
LC50 inhalation rat	29.08 mg/l/4h
ATE CA (oral)	3500 mg/kg bodyweight
ATE CA (Dermal)	1700 mg/kg bodyweight
ATE CA (vapours)	27.57 mg/l/4h
ATE CA (dust,mist)	29.08 mg/l/4h
Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat	17.4 mg/l/4h
ATE CA (oral)	3500 mg/kg bodyweight
ATE CA (Dermal)	15400 mg/kg bodyweight
ATE CA (Gases)	4500 ppmv/4h
ATE CA (vapours)	17.4 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
Kerosine, petroleum (8008-20-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.28 mg/l/4h
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
LD50 oral rat	8400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 6193 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:
LC50 inhalation rat	3400 ppm/4h

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Solvent naphtha, petroleum, light aromatic (64742-95-6)	
ATE CA (oral)	8400 mg/kg bodyweight
ATE CA (Gases)	3400 ppmv/4h
Benzene, 1,2,4-trimethyl- (95-63-6)	
LD50 oral rat	3280 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat	18 g/m ³ (Exposure time: 4 h)
ATE CA (oral)	3280 mg/kg bodyweight
ATE CA (Gases)	4500 ppmv/4h
ATE CA (vapours)	18 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
Isopropylbenzene (98-82-8)	
LD50 oral rat	1400 mg/kg
LD50 dermal rabbit	12300 µl/kg
LC50 inhalation rat	> 3577 ppm (Exposure time: 6 h)
ATE CA (oral)	1400 mg/kg bodyweight
ATE CA (Dermal)	12300 mg/kg bodyweight
Amides, C16-18 and C18-unsaturated, N,N-bis(hydroxyethyl) (68603-38-3)	
LD50 oral rat	> 3000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: other:A modification of the techniques described in Appraisal of the Safety of Chemicals in Foods, Drugs and Cosmetics, compiled by the staff of the Division of Pharmacology, Food and Drug Administration.
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified.
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Suspected of causing cancer.
Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen, Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes
Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable
Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes
Isopropylbenzene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Isopropylbenzene (98-82-8)	
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen, Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Suspected of damaging the unborn child.

Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
NOAEL (animal/male, F0/P)	35 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:
NOAEL (animal/female, F0/P)	125 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:

Naphthalene (91-20-3)	
LOAEL (animal/female, F0/P)	50 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:
LOAEL (animal/female, F1)	450 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:
NOAEL (animal/female, F0/P)	120 mg/kg bodyweight Animal: rabbit, Animal sex: female, Guideline: other:

Kerosine, petroleum (8008-20-6)	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]

STOT-single exposure : Not classified.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
STOT-single exposure	May cause drowsiness or dizziness.

Solvent naphtha, petroleum, light aromatic (64742-95-6)	
STOT-single exposure	May cause drowsiness or dizziness.

Benzene, 1,2,4-trimethyl- (95-63-6)	
STOT-single exposure	May cause respiratory irritation.

Isopropylbenzene (98-82-8)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified.

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
LOAEL (dermal, rat/rabbit, 90 days)	200 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
LOAEC (inhalation, rat, vapour, 90 days)	4.71 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	2000 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEC (inhalation, rat, vapour, 90 days)	2355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
Naphthalene (91-20-3)	
LOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
LOAEC (inhalation, rat, vapour, 90 days)	0.011 mg/l air Animal: rat, Guideline: EPA OPP 82-4 (90-Day Inhalation Toxicity), Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
Ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Kerosine, petroleum (8008-20-6)	
NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Benzene, 1,2,4-trimethyl- (95-63-6)	
NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	1.8 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
Amides, C16-18 and C18-unsaturated, N,N-bis(hydroxyethyl) (68603-38-3)	
NOAEL (oral, rat, 90 days)	> 750 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

Aspiration hazard

: May be fatal if swallowed and enters airways.

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Diesel Treat	
Viscosity, kinematic	3.89 mm ² /s @ 40 °C (104 °F)
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause stomach distress, nausea or vomiting.
Chronic symptoms	: Suspected of causing cancer. Suspected of damaging the unborn child.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)	
LC50 - Fish [1]	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
LC50 - Fish [1]	8.41 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	4.7 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	2.9 mg/l Test organisms (species): other:
LC50 - Fish [2]	2.34 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
Naphthalene (91-20-3)	
LC50 - Fish [1]	5.74 – 6.44 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	2.16 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	1.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 - Crustacea [2]	1.96 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])
NOEC (chronic)	0.59 mg/l Test organisms (species): Daphnia pulex Duration: '125 d'
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 - Fish [1]	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 - Fish [2]	2.661 – 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 - Crustacea [2]	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
Ethylbenzene (100-41-4)	
LC50 - Fish [1]	11 – 18 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Ethylbenzene (100-41-4)	
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic crustacea	0.956 mg/l
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
LC50 - Fish [1]	9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [1]	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Benzene, 1,2,4-trimethyl- (95-63-6)	
LC50 - Fish [1]	7.19 – 8.28 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Isopropylbenzene (98-82-8)	
LC50 - Fish [1]	6.04 – 6.61 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	0.6 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	4.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 - Crustacea [2]	7.9 – 14.1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
NOEC (chronic)	0.35 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.38 mg/l Test organisms (species): other:D. rerio and P. promelas Duration: '28 d'
Amides, C16-18 and C18-unsaturated, N,N-bis(hydroxyethyl) (68603-38-3)	
LC50 - Fish [1]	1.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 - Crustacea [1]	≈ 3.2 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	0.24 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.32 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '28 d'

12.2. Persistence and degradability

Diesel Treat	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Diesel Treat	
Bioaccumulative potential	Not established.

Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
BCF - Fish [1]	61 – 159
Partition coefficient n-octanol/water	2.8 – 6.5 (at 23 °C (at pH 6.2)

Naphthalene (91-20-3)	
BCF - Fish [1]	36.5 – 168 (whole body w.w.)
Partition coefficient n-octanol/water	3.4 (at 25 °C (at pH 7-7.5)

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF - Fish [1]	0.6 – 15
Partition coefficient n-octanol/water	2.77 – 3.15
Ethylbenzene (100-41-4)	
BCF - Fish [1]	(15 dimensionless)
Partition coefficient n-octanol/water	3.6 (at 20 °C (at pH 7.84))
Benzene, 1,2,4-trimethyl- (95-63-6)	
Partition coefficient n-octanol/water	3.63
Isopropylbenzene (98-82-8)	
BCF - Fish [1]	(35.5 dimensionless)
Partition coefficient n-octanol/water	3.55 (at 23 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on global warming : No known effects from this product.
Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. The generation of waste should be avoided or minimized wherever possible.
Additional information : Handle empty containers with care because residual vapours are flammable.

SECTION 14: Transport information

In accordance with DOT / TDG

14.1. UN number

DOT NA No : UN1268
UN-No. (TDG) : UN3082

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Petroleum distillates, n.o.s.
Proper Shipping Name (TDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Solvent naphtha, petroleum, light aromatic ; Benzene, 1,2,4-trimethyl-)

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3
Hazard labels (DOT) : 3

Diesel Treat


Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015



TDG

Transport hazard class(es) (TDG) : 9
Hazard labels (TDG) : 9



IMDG

Transport hazard class(es) (IMDG) : This product is currently not packaged to comply with IMDG regulations. It is not intended to be shipped by sea

14.4. Packing group

Packing group (DOT) : III
Packing group (TDG) : III

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

Naphthalene (91-20-3)

Subject to reporting requirements of United States SARA Section 313
Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	100 lb
-----------	--------

Xylenes (o-, m-, p- isomers) (1330-20-7)

Subject to reporting requirements of United States SARA Section 313
Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	100 lb
-----------	--------

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Ethylbenzene (100-41-4)	
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	1000 lb

Benzene, 1,2,4-trimethyl- (95-63-6)	
Subject to reporting requirements of United States SARA Section 313	

Isopropylbenzene (98-82-8)	
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	5000 lb

Vinyl acetate (108-05-4)	
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	5000 lb
Section 302 EPCRA Reportable Quantity (RQ)	5000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb

Benzene (71-43-2)	
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	10 lb received an adjusted RQ of 10 lbs based on potential carcinogenicity in an August 14, 1989 final rule


Toluene (108-88-3)	
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	1000 lb

Potassium hydroxide (1310-58-3)	
CERCLA RQ	1000 lb

15.2. International regulations

No additional information available

15.3. US State regulations

 **WARNING:** This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Component	State or local regulations
Distillates, petroleum, hydrotreated light naphthenic(64742-53-6)	U.S. - Massachusetts - Right To Know List
Naphthalene(91-20-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Xylenes (o-, m-, p- isomers)(1330-20-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
1,3,5-Trimethylbenzene(108-67-8)	U.S. - Massachusetts - Right To Know List
Ethylbenzene(100-41-4)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
2-Ethylhexanol(104-76-7)	U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Kerosine, petroleum(8008-20-6)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Sulfur(7704-34-9)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Benzene, 1,2,4-trimethyl-(95-63-6)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Isopropylbenzene(98-82-8)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Vinyl acetate(108-05-4)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Benzene(71-43-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Toluene(108-88-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Potassium hydroxide(1310-58-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Revision date : 02/23/2024

Other information : None.

Diesel Treat

Safety Data Sheet


According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Full text of H-statements	
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Flam. Liq. 4	Flammable liquids, Category 4
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Indication of changes:

Changed item	Change	Comments
Composition/information on ingredients	Modified	V1.1 - 2018-04-23
Transport information	Modified	V2.1 - 2019-03-01
Composition/information on ingredients	Modified	V2.2 - 2020-03-09
Supplier logo	Modified	V2.3 - 2021-07-13
SDS update (formulation revision)	Modified	V3.3 - 2024-02-23

SDS HazCom 2012 - WHMIS 2015 (Nexreg) 2023

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.