



SECTION 1: IDENTIFICATION

- 1.1 Product identifier: Diesel Treat
Other means of identification:
Not available
- 1.2 Recommended use of the chemical and restrictions on use:
Relevant uses (Consumer use): Diesel Additive
Relevant uses (Professional users): Diesel Additive
Relevant uses (Industrial user): Diesel Additive
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Initial supplier identifier:
R.B. Howes & Co. Inc.
60 Ocean State Drive
02852 North Kingstown - RI - United States
Phone: 4012945500
SDS@howesproducts.com
www.howesproducts.com
- | | |
|--|---|
| <u>Manufacturer</u>
R.B. Howes & Co., Inc.
3511 North Ohio Street
Wichita, KS, 67219
USA
T 401-294-5500, 1-800 GET HOWES (438-4693) | <u>Distributor</u>
White Line Distributors
3625 Weston Rd Unit 24
North York, ON M9L 1V9 - Canada
T +1 416-747-8509 |
| <u>Manufacturer</u>
EMCO Chemical Packaging
2100 Commonwealth Ave.
North Chicago, IL 60064 - USA
T 847-689-2200 | <u>Distributor</u>
Associated Truckers Supply
44195 Yale Rd
Chilliwack, BC V2R 4H2 - Canada
T +1 604-795-5700 |
- 1.4 Emergency phone number: 703-527-3887
(CHEMTREC) 800-424-9300

SECTION 2: HAZARD IDENTIFICATION

2.1 Classification of the substance or mixture:

Classified in accordance with 29 CFR 1910.1200 (HCS 2024) and Part 2 of the Canadian Hazardous Products Regulations (HPR), as amended.

29 CFR 1910.1200 (HCS 2024) / WHMIS 2022 (HPR):

Acute toxicity (inhalation), Category 4, H332
Aspiration hazard, Category 1, H304
Carcinogenicity, Category 1B, H350
Flammable liquids, Category 4, H227
Skin corrosion/irritation, Category 2 (skin irritation), H315
Specific target organ toxicity - single exposure, Category 3 (narcotic effects), H336

2.2 Label elements:



Signal word: Danger

Required workplace pictograms: Exclamation mark; Health hazard

Hazard statements:

H332 Harmful if inhaled.
H304 May be fatal if swallowed and enters airways.
H350 May cause cancer.
H227 Combustible liquid.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapors or mist.
P264 Wash hands and exposed skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing and eye protection. Use face protection where splash exposure is possible.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P331 Do NOT induce vomiting.
P302+P352 IF ON SKIN: Wash with plenty of water.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P304+P340+P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
P308+P313 IF exposed or concerned: Get medical advice/attention.



Safety data sheet
According to 29 CFR 1910.1200 (HCS 2024) and WHMIS
2022 (SOR/2022-272)
Diesel Treat

P370+P378 In case of fire: Use foam, dry chemical powder or carbon dioxide to extinguish.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/container in accordance with applicable local, regional, national and international regulations.

2.3 Hazards not otherwise classified / Other hazards:

United States - Hazards associated with known or reasonably anticipated uses resulting from chemical reactions under 29 CFR 1910.1200(d)(1)(ii): None Identified.
United States - Hazards not otherwise classified (HNOC): Non-applicable.
Canada - Health and physical hazards not otherwise classified (HHNOC - PHNOC): Not available.
Canada - Other hazards known to the supplier: Not available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances: Not applicable (mixture).

3.2 Mixtures: Mixture composed of additives in solvents.

CAS / unique identifier	Chemical name	Concentration (%)
8008-20-6	Kerosine (petroleum)	30 - <60%
64742-47-8	Distillates (petroleum), hydrotreated light	10 - <30%
64742-53-6	Distillates (petroleum), hydrotreated light naphthenic, <3% IP 346, <20.5 cSt @ 40°C	10 - <30%
64742-95-6	Solvent naphtha (petroleum), light aromatic, <0.1% EC 200-753-7	5 - <10%
95-63-6	1,2,4-Trimethylbenzene	1 - <5%
64742-94-5	Hydrocarbons, C10-C13, aromatics, >1% naphthalene	1 - <5%
98-82-8	Cumene	<1%
91-20-3	Naphthalene	<1%
98-94-2	Cyclohexyldimethylamine	<1%

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with 29 CFR 1910.1200(i)

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

Inhalation: Remove the affected person from the area of exposure, provide fresh air, and keep at rest. In severe cases such as cardiorespiratory arrest, trained personnel may provide appropriate resuscitation and should obtain immediate medical assistance.

Skin contact: Remove contaminated clothing and footwear. Wash affected skin with plenty of water and neutral soap. If irritation is serious or persists, obtain medical advice/attention. Wash contaminated clothing before reuse.

Eye contact: Rinse thoroughly with water for at least 15 minutes. Remove contact lenses if present and easy to do. Continue rinsing and obtain medical advice if irritation persists.

Ingestion / aspiration: Request medical assistance immediately. Do NOT induce vomiting. If vomiting occurs spontaneously, keep the head down to reduce aspiration risk. Never give anything by mouth to an unconscious person. Rinse the mouth and throat and keep the affected person at rest.

4.2 Most important symptoms/effects, acute and delayed: Skin irritation; harmful effects if inhaled; central nervous system effects including drowsiness or dizziness; aspiration into the lungs may be fatal. See Sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary: Aspiration hazard requires prompt medical evaluation following ingestion.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable extinguishing media: Foam, dry chemical powder, or carbon dioxide.

Unsuitable extinguishing media: Do not use a direct water jet.

5.2 Specific hazards arising from the chemical: Combustible liquid. Combustion or thermal decomposition can generate carbon monoxide, carbon dioxide and other irritating or toxic organic decomposition products.

5.3 Special protective equipment and precautions for fire-fighters: Wear full protective clothing and self-contained breathing apparatus. Evacuate nonessential personnel, remove ignition sources, cool exposed containers from a safe distance where appropriate, and prevent fire-fighting runoff from entering waterways.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures: Evacuate unnecessary personnel. Eliminate ignition sources. Provide adequate ventilation. Prevent formation of flammable vapor-air mixtures. Wear appropriate PPE as described in Section 8. Ground and bond conductive equipment where static accumulation is possible.

6.2 Environmental precautions: Prevent entry into drains, sewers, surface water and groundwater. Contain released material and notify the appropriate authority if a release threatens the public or environment.

6.3 Methods and materials for containment and cleaning up: Absorb with sand or other inert noncombustible absorbent and place in suitable closed containers for disposal. Do not use sawdust or other combustible absorbents. For releases to water, use barriers or other appropriate containment and mechanical recovery methods; obtain required approvals before using dispersants.

United States reporting: For releases exceeding applicable reportable quantities, refer to 40 CFR 302 and notify the National Response Center at 800-424-8802 as required.

6.4 Reference to other sections: See Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling: Keep containers tightly closed. Avoid skin contact and breathing vapors or mist. Use adequate ventilation. Keep away from ignition sources. Transfer slowly and ground/bond equipment where static accumulation is possible. Do not eat or drink while handling; wash after use. Follow applicable U.S. and Canadian occupational health and safety requirements.

7.2 Conditions for safe storage, including incompatibilities: Store in a cool, dry, well-ventilated location. Keep container tightly closed and store locked up. Protect from heat, ignition sources, direct sunlight, static discharge and incompatible materials. Keep away from food.

7.3 Specific end use(s): Diesel additive. No additional recommendations beyond those specified in this SDS.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substance	U.S. OSHA PEL	ACGIH TLV (2022 source)	British Columbia	Alberta	Ontario
Kerosine (petroleum) (8008-20-6)	--	200 mg/m ³ TWA	200 mg/m ³ TWA	200 mg/m ³ 8-h	--



Safety data sheet
According to 29 CFR 1910.1200 (HCS 2024) and WHMIS
2022 (SOR/2022-272)
Diesel Treat

Substance	U.S. OSHA PEL	ACGIH TLV (2022 source)	British Columbia	Alberta	Ontario
1,2,4-Trimethylbenzene (95-63-6)	--	10 ppm TWA	25 ppm TWA	25 ppm (123 mg/m ³) 8-h	--
Mesitylene (108-67-8)	--	10 ppm TWA	25 ppm TWA	25 ppm (123 mg/m ³) 8-h	--
Xylene* (1330-20-7)	100 ppm (435 mg/m ³) TWA	20 ppm TWA	100 ppm TWA; 150 ppm STEL	100 ppm (434 mg/m ³) 8-h; 150 ppm (651 mg/m ³) 15-min	--
1,2,3-Trimethylbenzene (526-73-8)	--	10 ppm TWA	25 ppm TWA	25 ppm (123 mg/m ³) 8-h	--
Cumene* (98-82-8)	50 ppm (245 mg/m ³) TWA	5 ppm TWA	25 ppm TWA; 75 ppm STEL	50 ppm (246 mg/m ³) 8-h	--
Ethylbenzene* (100-41-4)	100 ppm (435 mg/m ³) TWA	20 ppm TWA	20 ppm TWA	100 ppm (434 mg/m ³) 8-h; 125 ppm (543 mg/m ³) 15-min	--
Naphthalene (91-20-3)	10 ppm (50 mg/m ³) TWA	10 ppm TWA	10 ppm TWA	10 ppm (52 mg/m ³) 8-h; 15 ppm (79 mg/m ³) 15-min	--
Cyclohexyldimethylamine (98-94-2)	--	--	--	--	5 ppm (26 mg/m ³) STEL

8.2 Appropriate engineering controls: Use adequate general or local ventilation and other engineering controls as necessary to maintain airborne concentrations below applicable occupational exposure limits. Conduct a workplace hazard assessment for the task and jurisdiction.

Respiratory protection: If engineering controls cannot maintain airborne concentrations below applicable limits or acceptable levels, use suitable respiratory protection selected by a qualified professional.

Hand protection: Wear chemical-resistant protective gloves suitable for hydrocarbon/solvent exposure; select glove material and breakthrough time for the task using manufacturer information.

Eye/face protection: Wear safety glasses with side shields. Use chemical splash goggles and/or a face shield where splash exposure is possible.

Body protection: Wear protective clothing as needed to prevent skin contact. Remove contaminated clothing and wash before reuse.

Environmental exposure controls: Prevent uncontrolled release to the environment. Use containment where spills could enter drains or waterways.

Volatile organic compounds (VOC): 68.42% by weight.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Property	Value
Physical state	Liquid
Appearance	Amber
Color / colour	Amber
Odor / odour	Characteristic
Odor threshold	Not available
Melting point/freezing point	Not available
Boiling point / initial boiling point / range	Not available
Flammability	Combustible liquid
Lower/upper flammability or explosive limits	Not available
Flash point	>66 °C (>150 °F)
Autoignition temperature	Not available
Decomposition temperature	Not available
pH	Not available
Kinematic viscosity	≤20.5 mm ² /s at 40 °C (104 °F)
Solubility in water	Insoluble
Partition coefficient (n-octanol/water)	Not available
Vapor pressure	Not available
Relative vapor density	Not available
Density	835.5 kg/m ³ at 20 °C (68 °F)
Relative density	0.86 at 20 °C / 68 °F
Particle characteristics	Not applicable - liquid

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity: No hazardous reactions are expected because the product is stable under recommended storage conditions. See Section 7.

10.2 Chemical stability: Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions: Under the specified conditions, hazardous reactions leading to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid: Avoid increased temperature, heat and ignition sources, and direct sunlight. See Section 7.

10.5 Incompatible materials: Avoid strong acids, oxidizing materials, alkalis and strong bases.

10.6 Hazardous decomposition products: Depending on decomposition conditions, carbon dioxide, carbon monoxide and other organic compounds may be released.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects: The experimental information related to the toxicological properties of the product itself is not available.

Likely routes of exposure: Ingestion, inhalation, skin contact and eye contact.

Symptoms related to physical, chemical and toxicological characteristics: Reported effects include throat irritation, abdominal pain, nausea and vomiting after ingestion; headache, dizziness, vertigo, nausea, vomiting, confusion and, in serious cases, loss of consciousness after high inhalation exposure; and skin inflammation after contact.

Delayed and immediate effects; chronic effects: In case of repetitive or prolonged exposure, or exposure at concentrations higher than recommended occupational exposure limits, adverse health effects may occur depending on the route of exposure. Endpoint-specific information is provided below.

Substance	Oral	Dermal	Inhalation
Kerosine (petroleum) (CAS 8008-20-6)	LD50 5500 mg/kg (rat)	LD50 5500 mg/kg (rabbit)	Not available
Solvent naphtha (petroleum), light aromatic (CAS 64742-95-6)	LD50 2100 mg/kg (rat)	LD50 2000 mg/kg (rabbit)	Not available
1,2,4-Trimethylbenzene (CAS 95-63-6)	LD50 3400 mg/kg (rat)	LD50 3160 mg/kg (rabbit)	LC50 inhalation vapor 10.2 mg/L (rat)
Cyclohexyldimethylamine (CAS 98-94-2)	LD50 289 mg/kg (rat)	LD50 380 mg/kg (rat)	LC50 inhalation vapor 3 mg/L



Safety data sheet
According to 29 CFR 1910.1200 (HCS 2024) and WHMIS
2022 (SOR/2022-272)
Diesel Treat

Substance	Oral	Dermal	Inhalation
Cumene (CAS 98-82-8)	LD50 2700 mg/kg	Not available	Not available
Naphthalene (CAS 91-20-3)	LD50 533 mg/kg (rat)	LD50 16000 mg/kg (rat)	Not available

Mixture acute toxicity estimate (ATE): Not available. No new mixture ATE was calculated.

Interactive effects: No relevant interaction information is readily available in the controlled source SDSs.

Carcinogenicity listings: Cumene and Naphthalene are identified in NTP / regulatory carcinogen information and California Proposition 65 cancer listings. No OSHA specifically regulated carcinogen is identified.

Alternative information / methodology: Where product-specific data are unavailable, classification and toxicological conclusions are based on available component data, read-across where appropriate, and the mixture classification rules applicable under HCS 2024 and the HPR.

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available.

Supplemental environmental classification: Acute Category 2 and Aquatic long-term Category 2

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Acute toxicity:

Identification		Concentration	Species	Genus
Distillates (petroleum), hydrotreated light	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
Solvent naphtha (petroleum), light aromatic, <0.1% EC 200-753-7	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
1,2,4-Trimethylbenzene	LC50	7.72 mg/L (96 h)	Pimephales promelas	Fish
	EC50	6.14 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Not available		Algae
Hydrocarbons, C10-C13, aromatics, >1% naphthalene	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
Cumene	LC50	2.7 mg/L (96 h)	Salmo gairdneri	Fish
	EC50	10.8 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	2.6 mg/L (72 h)	Selenastrum capricornutum	Algae
Naphthalene	LC50	1.6 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	2.2 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Not available		Algae
Cyclohexyldimethylamine	LC50	28 mg/L (96 h)	Leuciscus idus	Fish
	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	2 mg/L (72 h)	Desmodesmus subspicatus	Algae

Chronic toxicity:

Identification		Concentration	Species	Genus
Cumene	NOEC	0.38 mg/L	Pimephales promelas	Fish
	NOEC	0.35 mg/L	Daphnia magna	Crustacean
Naphthalene CAS: 91-20-3	NOEC	0.37 mg/L	Oncorhynchus kisutch	Fish
	NOEC	0.59 mg/L	Daphnia pulex	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification		Degra Value	Biodegradabilit	Value
Solvent naphtha (petroleum), light aromatic, <0.1% EC 200-753-7	BOD5	0.19 g O2/g	Concentration	Not available
	COD	0.44 g O2/g	Period	Not available
	BOD5/COD	0.43	% Biodegradable	Not available
1,2,4-Trimethylbenzene	BOD5	Not available	Concentration	100 mg/L
	COD	Not available	Period	28 days
	BOD5/COD	Not available	% Biodegradable	18 %
Cumene	BOD5	Not available	Concentration	100 mg/L
	COD	Not available	Period	14 days
	BOD5/COD	Not available	% Biodegradable	40 %
Naphthalene	BOD5	Not available	Concentration	Not available
	COD	Not available	Period	28 days



Safety data sheet
According to 29 CFR 1910.1200 (HCS 2024) and WHMIS
2022 (SOR/2022-272)
Diesel Treat

	BOD5/COD	Not available	% Biodegradable	74 %
Cyclohexyldimethylamine CAS: 98-94-2	BOD5	Not available	Concentration	20 mg/L
	COD	Not available	Period	28 days
	BOD5/COD	Not available	% Biodegradable	95 %

SECTION 12: ECOLOGICAL INFORMATION (continued)

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccum	Value
Kerosine (petroleum)	BCF	5800
	Pow Log	5.25
	Potential	Very High
Distillates (petroleum), hydrotreated light	BCF	130
	Pow Log	3.3
	Potential	High
Solvent naphtha (petroleum), light aromatic, <0.1% EC 200-753-7	BCF	Not available
	Pow Log	4
	Potential	Not available
1,2,4-Trimethylbenzene	BCF	154
	Pow Log	3.78
	Potential	High
Cumene	BCF	120
	Pow Log	3.66
	Potential	High
Cyclohexyldimethylamine	BCF	Not available
	Pow Log	2.31
	Potential	Not available

12.4 Mobility in soil:

Identification	Absorpti	Value	Volatili	Value
1,2,4-Trimethylbenzene	Koc	537	Henry	624.16 Pa·m ³ /mol
	Conclusion	Low	Dry soil	Yes
	Surface tension	2.919E-2 N/m (25 °C)	Moist soil	Yes
Cumene	Koc	Not available	Henry	Not available
	Conclusion	Not available	Dry soil	Not available
	Surface tension	2.769E-2 N/m (25 °C)	Moist soil	Not available
Naphthalene	Koc	Not available	Henry	Not available
	Conclusion	Not available	Dry soil	Not available
	Surface tension	1.306E-2 N/m (277.74 °C)	Moist soil	Not available
Cyclohexyldimethylamine	Koc	69.49	Henry	6.73 Pa·m ³ /mol
	Conclusion	High	Dry soil	Not available
	Surface tension	Not available	Moist soil	Not available

12.5 Results of PBT and vPvB assessment:

Not available.

12.6 Other adverse effects:

Not described.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods: Do not discharge product or waste to drains. Dispose of product, contaminated absorbents and containers through an authorized waste service in accordance with applicable federal/national, state/provincial and local requirements. Empty containers may retain hazardous residues.

United States: Evaluate waste under the RCRA framework and applicable EPA requirements. State requirements may be more stringent. Household wastes generated by normal household activities are excluded as described in 40 CFR 261.4.

Canada: Manage waste in accordance with applicable federal/provincial requirements, including the Canadian Environmental Protection Act, 1999.

SECTION 14: TRANSPORT INFORMATION

14.1-14.7 United States - U.S. DOT / 49 CFR:

Item	U.S. DOT information
UN / identification number	UN1268
Proper shipping name	PETROLEUM PRODUCTS, N.O.S.
Hazard class	Combustible Liquid



Safety data sheet
According to 29 CFR 1910.1200 (HCS 2024) and WHMIS
2022 (SOR/2022-272)
Diesel Treat

Item	U.S. DOT information
Packing group	III
Marine pollutant	Yes
Special precautions / other source information	Limited quantities: 5 L. Under 49 CFR 171.4, marine-pollutant requirements do not apply to specified non-bulk packages transported by motor vehicle, rail car or aircraft except when transported aboard a vessel. Transport in bulk under MARPOL/IBC: Non-applicable.

Canada - TDG:

Item	Canada TDG information
UN number	UN3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hydrocarbons, C10-C13, aromatics, >1% naphthalene, Kerosine)
Class	9
Packing group	III
Environmental hazard	Yes
Special precautions / bulk	Physico-chemical properties: see Section 9. Transport in bulk under MARPOL/IBC: Not available.

Sea - IMDG 42-24: UN1268; PETROLEUM PRODUCTS, N.O.S.; Class 3; label 3; Packing Group III; Marine pollutant: Yes. Special provisions: 223, 955, 363. EmS: F-E, S-E. Limited quantity: 5 L. Segregation group: Not available. Transport in bulk under MARPOL/IBC: Not available.

Air - IATA/ICAO 2025: UN1268; PETROLEUM PRODUCTS, N.O.S.; Class 3; label 3; Packing Group III; Environmental hazard: Yes. Physico-chemical properties: see Section 9. Transport in bulk under MARPOL/IBC: Not available.

Transport limitations: This product is not packaged or prepared for transport in accordance with IMDG or IATA/ICAO requirements and is not intended to be shipped by sea or air.

SECTION 15: REGULATORY INFORMATION

15.1 United States:

- OSHA specifically regulated substances (29 CFR 1910.1001-1096): Non-applicable.
- Toxic Substances Control Act (TSCA): All components are listed or exempt.
- EPCRA Section 313 (40 CFR Part 372): 1,2,4-Trimethylbenzene (95-63-6); Cumene (98-82-8); Naphthalene (91-20-3).
- CERCLA reportable substances: Cumene (98-82-8) - U055; Naphthalene (91-20-3) - U165.
- Clean Air Act hazardous air pollutants: Cumene (98-82-8); Naphthalene (91-20-3).
- California Proposition 65 - Cancer: Cumene (98-82-8); Naphthalene (91-20-3).
- California Proposition 65 - Birth defects or other reproductive harm: Non-applicable.
- California Labor Code - Hazardous Substances List: 1,2,4-Trimethylbenzene (95-63-6); Cumene (98-82-8); Naphthalene (91-20-3).
- Massachusetts RTK - Substance List: Kerosine (petroleum); distillates (petroleum), hydrotreated light naphthenic; solvent naphtha (petroleum), light aromatic; 1,2,4-trimethylbenzene; hydrocarbons, C10-C13, aromatics, >1% naphthalene; cumene; naphthalene.
- Pennsylvania Worker and Community Right-to-Know Law: Kerosine (petroleum); distillates (petroleum), hydrotreated light naphthenic; solvent naphtha (petroleum), light aromatic; hydrocarbons, C10-C13, aromatics, >1% naphthalene; naphthalene.
- Rhode Island - Hazardous substances RTK: Cumene (98-82-8); Naphthalene (91-20-3).

15.1 Canada:

- Domestic Substances List (DSL): Disclosed components are listed as applicable.
- National Pollutant Release Inventory (NPRI) 2025-2027: light aromatic solvent naphtha, 1,2,4-trimethylbenzene, cumene, naphthalene, heavy aromatic solvent naphtha and hydrotreated light distillates.
- First Priority Substances List (PSL1): Naphthalene.
- Toxic substances list - Part 2: Naphthalene.
- Canadian Environmental Protection Act, 1999.
- Other applicable federal, state/provincial and local requirements may apply.

SECTION 16: OTHER INFORMATION

Regulatory basis: Prepared to address the information requirements of 29 CFR 1910.1200, including Appendices C and D (HCS 2024), and Part 4 / Schedule 1 of the Canadian Hazardous Products Regulations, including amendments under SOR/2022-272.

Date of compilation: 2025-12-02

Revision date: 2026-08-25

Disclaimer: The information contained in this safety data sheet is based on the controlled supplier source SDSs, technical knowledge and current regulatory references. This information is not a guarantee of product properties; it is a description of safety requirements. Occupational methods and conditions of use are outside the supplier's direct control. The information in this SDS refers only to this product and the uses specified herein.